



**Staki** is a long established flooring producer situated in Lithuania. All products are made using a European top layer adhered to a birch plywood base. The boards are 2.4m in length and are substantial floors designed to last.

If you want to elevate the look of the floors in your home, without losing the light airy feel of your home, consider light flooring to your space. The **Chester**, combines the elegance of a light floor with a touch of silver to enhance the grain.



### RUSTIC GRADING DESCRIPTION

**Staki Rustic floors can contain the following:**

- Sound knots up to 90mm diameter
- Filled knots up to 50mm diameter
- Quantity of knots are not limited
- Small cracks on the surface of board
- All cracks and knots can be filled
- Natural colour variation

### FLOORING SPECIFICATION

|                |                                                |
|----------------|------------------------------------------------|
| Species        | Oak                                            |
| Grade          | Rustic                                         |
| Design         | Plank                                          |
| Construction   | Engineered                                     |
| Dimensions mm  | 220W x 15T x 2400L<br>or<br>180W x 15T x 2400L |
| Wear Layer     | 4mm                                            |
| Bevels         | 2 (on long sides)                              |
| Surface Finish | LED Oil                                        |
| Joint Type     | Tongue & Groove                                |
| Base Layer     | Birch Plywood                                  |
| Warranty       | 12 Years Residential<br>10 Years Commercial    |

### INSTALLATION

|                     |                |
|---------------------|----------------|
| Acclimatisation     | 2 days on site |
| Humidity            | 30-65%         |
| Underfloor Heating  | Compatible     |
| UFH Temperature     | < 27°C         |
| Installation Method | Fully bonded   |

\* Full installation guide available

### MAINTENANCE

|                   |                                 |
|-------------------|---------------------------------|
| Protection        | Entrance matting/furniture feet |
| Daily Cleaning    | Dry mop                         |
| Regular Cleaning  | Osmo Wash & Care                |
| Periodic Cleaning | Osmo Liquid Wax Cleaner         |

### PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density: 500kg m<sup>3</sup>
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm  
BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK  
R.N. 046/15-3
- Biological durability: 1 class  
BS EN 14342:2013