



Staki is a long established flooring producer situated in Lithuania. All products are made using a European top layer adhered to a birch plywood base. The boards are 2.4m in length and are substantial floors designed to last.

One of the most admired attributes of an oak floor is its attractive grain structure. The subtle colouring deepens and as a natural material, it becomes part of the room. The warm, golden hue of an oak floor makes it a firm favourite.



SELECT GRADING DESCRIPTION

Staki Select floors can contain the following:

- Healthy, cracked, not fallen out knots till 8-10 mm
- Rare occurred fallen out knots till 8 mm
- Rare occurred light timber colour variation, white spots
- Knots are filled
- Please note that Staki Select grade floors do not contain sapwood

FLOORING SPECIFICATION

Species	Oak
Grade	Select
Design	Plank
Construction	Engineered
Dimensions mm	220W x 15T x 2400L or 180W x 15T x 2400L
Wear Layer	4mm
Bevels	2 (on long sides)
Surface Finish	LED Oil
Joint Type	Tongue & Groove
Base Layer	Birch Plywood
Warranty	12 Years Residential 10 Years Commercial

INSTALLATION

Acclimatisation	2 days on site
Humidity	30-65%
Underfloor Heating	Compatible
UFH Temperature	< 27°C
Installation Method	Fully bonded

* Full installation guide available

MAINTENANCE

Protection	Entrance matting/furniture feet
Daily Cleaning	Dry mop
Regular Cleaning	Osmo Wash & Care
Periodic Cleaning	Osmo Liquid Wax Cleaner

PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density: 500kg m³
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm
BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK
R.N. 046/15-3
- Biological durability: 1 class
BS EN 14342:2013