

Rosewood LED Oil SELECT

Technical Data Sheet



Staki is a long established flooring producer situated in Lithuania. All products are made using a European top layer adhered to a birch plywood base. The boards are 2.4m in length and are substantial floors designed to last.

Warm-coloured flooring can complement various design styles, from traditional to contemporary, and can pair well with a range of decor options, including earthy neutrals, vibrant accents, or rustic elements.



SELECT GRADING DESCRIPTION

Staki Select floors can contain the following:

- Healthy, cracked, not fallen out knots till 8-10 mm
- Rare occurred fallen out knots till 8 mm
- Rare occurred light timber colour variation, white spots
- Knots are filled
- Please note that Staki Select grade floors do not contain sapwood

FLOORING SPECIFICATION

Species	Oak
Grade	Select
Design	Plank
Construction	Engineered
Dimensions mm	220W x 15T x 2400L or 180W x 15T x 2400L
Wear Layer	4mm
Bevels	2 (on long sides)
Surface Finish	LED Oil
Joint Type	Tongue & Groove
Base Layer	Birch Plywood
Warranty	12 Years Residential 10 Years Commercial

INSTALLATION

Acclimatisation	2 days on site
Humidity	30-65%
Underfloor Heating	Compatible
UFH Temperature	< 27°C
Installation Method	Fully bonded

* Full installation guide available

MAINTENANCE

Protection	Entrance matting/furniture feet
Daily Cleaning	Dry mop
Regular Cleaning	Osmo Wash & Care
Periodic Cleaning	Osmo Liquid Wax Cleaner

PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density: 500kg m3
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm
BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK
R.N. 046/15-3
- Biological durability: 1 class
BS EN 14342:2013