

Smoked LED Oil Herringbone

Technical Data Sheet



Staki is a long established flooring producer situated in Lithuania. All products are made using a European top layer adhered to a birch plywood base. Distinct pattern created with 500 x 100mm 15mm rectangular engineered boards.

The second in our 'smoked' range, this floor is full of character and tirelessly interesting to look at. The literal smoking of this floor gives it a depth of colour not easily replicated, not even from batch to batch, ensuring you have a truly unique floor.



HERRINGBONE GRADING DESCRIPTION

Herringbone floors can contain the following:

- Sound knots up to 30mm diameter
- Knots can be sprung, but filled
- Permitted fallen out knots to 15mm
- Quantity of knots are not limited
- Small cracks on the surface of board
- All cracks are filled
- Natural colour variation, white spots
- Due to this floor being smoked, please note that the colour variation between boards will differentiate more than a typical oak floor

FLOORING SPECIFICATION

Species	Oak
Grade	Rustic
Design	Herringbone
Construction	Engineered
Dimensions mm	100W x 15T x 500L
Wear Layer	4mm
Bevels	4
Surface Finish	LED Oil
Joint Type	Tongue & Groove
Base Layer	Birch Plywood
Warranty	25 years

INSTALLATION

Acclimatisation	2 days on site
Humidity	30-65%
Underfloor Heating	Compatible
UFH Temperature	< 27°C
Installation Method	Fully bonded

* Full installation guide available

MAINTENANCE

Protection	Entrance matting/furniture feet
Daily Cleaning	Dry mop
Regular Cleaning	Osmo Wash & Care
Periodic Cleaning	Osmo Liquid Wax Cleaner

PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density: 500kg m³
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm
BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK
R.N. 046/15-3
- Biological durability: 1 class
BS EN 14342:2013